



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF DYTRAN INSTRUMENTS INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF DYTRAN INSTRUMENTS INC. IS PROHIBITED

REVISIONS

REV	ECN	DESCRIPTION	BY/DATE	CHK	APPR
A	6348	INITIAL RELEASE	JLS 11/03/09	DV	ANS
B	11075	ADDED CABLE I.D. LABEL, PIGTAIL END	LN 06/06/14	MH	



6. JACKET PFA .006 WALL NOMINAL, COLOR WHITE.
5. VOLTAGE RATING 250 VOLTS.
4. SHIELDING SILVER PLATED COPPER BRAID, 90% MIN COVERAGE.
3. 4 CONDUCTOR 32 AWG 7/38 SILVER PLATED COPPER, FEP.
2. TEMPERATURE RANGE:-18 °C TO 176 °C.

1 PART NUMBER: 6895AXX (XX DENOTES LENGTH IN FEET).

NOTES: UNLESS OTHERWISE SPECIFIED

<p>UNLESS OTHERWISE SPECIFIED: INTERPRET DIM & TOL PER ASME Y14.5M - 1994. REMOVE BURRS. COUNTERSINK INTERNAL THDS 90° TO MAJOR DIA. CHAM EXT THDS 45° TO MINOR DIA. THD LENGTHS AND DEPTHS ARE FOR MIN FULL THDS. THDS PER MIL-S-7742. DIMENSIONS APPLY AFTER FINISHING.</p>		<p>UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES. DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS TOLERANCES ARE: INCHES METRIC ANGLES .XX ± .03 X ± 0.8 ± 1° .XXX ± .010 .XX ± 0.25</p>		<p>CONTRACT NO.</p>		<p>DYTRAN INSTRUMENTS, INC. Chatsworth, CA</p>	
USED ON	NEXT ASSY	MATERIAL		APPROVALS		DATE	
APPLICATION		FINISH		ORIG		JS 10/29/09	
THIRD ANGLE PROJECTION USA		DO NOT SCALE DRAWING		CHK		DV 11/06/09	
<p>ALL MACHINED SURFACES. TOTAL RUNOUT WITHIN .005. BREAK SHARP EDGES .005 TO .010. MACHINED FILLET RADII .005 TO .015. WELDING SYMBOLS PER AWS A2.4. ABBREVIATIONS PER MIL-STD-12.</p>				APP		ANS 11/06/19	
				APP		6/10/11	
<p>TITLE: OUTLINE/INSTALLATION DRAWING 6895A</p>				<p>SIZE: A</p>		<p>CAGE CODE: 2W033</p>	
				<p>DWG. NO.: 127-6895A</p>		<p>REV: B</p>	
<p>SCALE: NONE</p>				<p>SOLIDWORKS</p>		<p>SHEET 1 OF 1</p>	